# ACT 73 BMF

# **Boiler Water Treatment**

ACT 73 BMF is a fully formulated sodium sulfite boiler treatment solution. This product neutralizes pH, controls hard water scale, and prevents rust formation all in 1 product. Easy to dilute and add to boiler water. Can be easily titrated to verify proper concentation.

- \* Complete Boiler Treatment in 1 Product
- · Easy to Use

- Economical Formulation
- · Easy to Measure

**Usage Directions:** Add ACT 73 BMF to boiler feed water at rate of 1 gallon per 1000 gallons water. This will provide the industry standard 25 ppm Sodium Sulfite. Verify concentration with Sulfite Test Kit (MRTK3502-Z)

# Safety & Hazards



Wear Protective Eye Glasses, Chemical-Resistant Gloves and Waterproof Apron While Using ACT 73 BMF

**Consult SDS for Further Safety Precautions** 

**DOT Shipping Name:** Not Regulated

## **Technical Information:**

Appearance: Yellow Liquid Transparent

Odor: None pH: 10.5-11.5 Foam: Non-Foaming

ACT 73 BMF Dilution Guidelines	
Usage	Dilution
Normal Usage	1 Gallon per 1000 gallons water (25 ppm Na2 SO4)

### **Titration Kit:**

MRTK3502-Z, Sulfite Titration Sulfite Titrant Low 1 drop = 2 ppm as Sodium Sulfite Sulfite Titrant High 1 Drop = 10 ppm as Sodium Sulfite

Pounds Per Gallon: 9.16