

Clor VL

Heavy Duty Powdered CIP Detergent with Bleach

Clor VL is a heavy duty, low-foaming CIP detergent effective on oils, grease, sugary and proteinaceous soils. Clor VL can be used for CIP and spray cleaning of process tanks and hot milk lines in dairies, as a HTST cleaner in bakeries or a soak cleaner in food processing plants. Clor VL can be mixed with Detergent Concentrate when foaming applications are needed.

- **Heavy Duty Detergent with Bleach**
- **Useful in Industrial Dishwashing Machines**
- **Low-Foaming**
- **Rinses Easily**

Usage Directions: Dilute Clor VL in accordance with Dilution Guidelines chart.

CIP applications: Flush pipes with fresh water to remove loose soils. Heat Clor VL solution to 140°-150°F. Circulate solution through pipes for 10 - 25 minutes, or until all soils are removed from pipelines. Flush lines with fresh water. Fill pipelines with appropriate sanitizer.

Soak Applications: Add appropriate amount of Clor VL to cleaning bath. Heat solution, when possible, to 140°-150°F. Allow parts to soak for 10 - 25 minutes, or until all soils are removed from parts. Rinse parts with fresh water and follow with appropriate sanitizer.

Dishwashing Machine: Add appropriate amount of Clor VL to dish machine manually or through powder dispenser. Clor VL works best when used with hot water. Follow with rinsing agent and sanitizing rinse.

Safety & Hazards



Wear Protective Eye Glasses, Chemical-Resistant Gloves, Dust & Vapor Respirator and Waterproof Apron While Using Clor VL

Consult SDS for Further Safety Precautions

DOT Shipping Name: UN3262, Corrosive solid, basic, inorganic, n.o.s. (Sodium Hydroxide & Sodium Metasilicate), 8, PG II.

Technical Information:

Appearance: Off-white. Free Flowing Granules.
Odor: Slight Chlorine Odor
pH: <13
Foam: Non-Foaming

Associated Products:

Detergent Concentrate, Heavy Duty Detergent & Foam Booster
MG 4-Quat, 5th Generation Quaternary Sanitizer & Disinfectant
MG Peracid 6, 5.6% Peroxyacetic Acid Sanitizer
Rinse Aid, Warewashing Rinse Additive & Sheeting Agent

Clor VL Dilution Guidelines

Usage	Dilution
CIP Applications	1 - 4 Oz per Gallon Water
Soak Applications	2 - 6 Oz per Gallon Water
Dishwashing Machines	1 - 2 Oz Per Gallon Water

Warning: Do Not Mix With Acidic Products. May Damage Painted Surfaces, Aluminum, Brass, Copper, Galvanized And/Or Other Soft Metals.

Products Manufactured By:

Morgan Gallacher, Inc.
SUPERIOR CLEANING PRODUCTS
8787 Millergrove Drive - Santa Fe Springs, CA 90670
(562) 695-1232 - FAX: (562) 699-8953