

Liquid B Brite

Non-Foaming Caustic Detergent

Liquid B Brite is a low-foam, high caustic liquid detergent for use in manual cleaning applications as well as automatic spray wash equipment including circulation (C.I.P.), pressure washing, boil-out, soak and fog cleaning. Liquid B Brite cuts through heavy grease & oil and rinses away easily and completely.

- **Extremely High Alkalinity**
- **Cuts Through Heavy Carbon and Grease**
- **Rinses Easily**
- **Effective in CIP, Dairy & Bottle Wash Applications**

Usage Directions: C.I.P. APPLICATIONS: Flush system with water. Prepare a solution of ½ to 6 oz of product per gallon of water, depending on the severity and type of soils. Circulate through the system until soils are loosened and/or removed as determined by inspection. Drain system and rinse thoroughly with potable water.

BOIL-OUT AND SOAK OPERATIONS: Dilute 3 to 12 oz of product per gallon of water. Heat solution and allow soaking until soils are loosened and/or removed as determined by inspection. Scrub or hand detail with a nylon pad or brush if necessary. Drain system and rinse thoroughly with potable water.

FOG CLEANING FOR OVENS AND SMOKEHOUSES: Warm smokehouse or oven to approximately 100°F(38°C) to 120°F(49°C). Dilute 10 - 20 oz of product per gallon of water. Apply product to all internal surfaces of the oven or smokehouse through the an appropriate fogger. Use the equipment's internal air handling system to circulate the fogged detergent. Allow product to settle or dissipate prior to opening the oven or smokehouse. Thoroughly rinse all surfaces with potable water.

Safety & Hazards



Wear Protective Eye Glasses, Chemical-Resistant Gloves and Waterproof Apron While Using Liquid B Brite

Consult SDS for Further Safety Precautions

DOT Shipping Name: UN 1823, Sodium Hydroxide Solution, 8, PG II

Technical Information:

Appearance: Clear Light Brown Liquid
Odor: None
pH: >13
Foam: Non-Foaming

Associated Products:

FCC-3, Foaming Chlorinated Detergent With Caustic & Rinse Agents
Detergent Concentrate, Heavy Duty Detergent & Foam Booster
MG Peracid 6, 5.6% Peroxyacetic Acid Sanitizer
MG 4-Quat, 5th Generation Quaternary Sanitizer & Disinfectant

Liquid B Brite

Dilution Guidelines

| Usage | Dilution |
|----------------|-----------------------|
| Clean-In-Place | ½ to 6 oz per Gallon |
| Boil-Out | 3 - 12 oz per Gallon |
| Fog Cleaning | 10 - 20 oz per Gallon |

Titration Kit:

MRTK3000-Z, High-Alkalinity / Caustic Titration
1 Drop = 0.255 oz per gallon

Warning: May Damage Painted Surfaces, Aluminum, Brass, Copper, Galvanized And/Or Other Soft Metals. Do Not Mix With Acidic Products.

Products Manufactured By:

Morgan Gallacher, Inc.
SUPERIOR CLEANING PRODUCTS
8787 Millergrove Drive - Santa Fe Springs, CA 90670
(562) 695-1232 - FAX: (562) 699-8953