

# Resque Plus

## Heavy Duty Degreaser With Caustic

Resque Plus is a heavy duty degreaser fortified with grease-cutting solvents and potassium hydroxide. This powerful combination penetrates through the heaviest of soils typically found in automotive shops, industrial applications, laundry facilities and food service & food processing establishments. Resque Plus is effective in cleaning stainless steel, floors, walls, hoods, ovens, grills, machinery, and many other surfaces. This product can also be used as a floor stripper to clean and prepare floors for sealing.

- **Cuts Through Heavy Grease & Oil**
- **Self-Foaming Solution**
- **Remains Effective in Hard Water**
- **Useful in Janitorial, Industrial, Automotive & Food Processing Environments**

**Usage Directions:** Dilute in accordance with Dilution Guidelines chart. Although not necessary, Resque Plus typically works better when diluted with warm to hot water, up to 160°F. Make sure to test a small area for compatibility with surfaces or fabrics before widespread use. Resque Plus can be applied by soak, spray, foam, or sponge. Some soils will require scrubbing. Extra heavy soils may require a re-application of the product. After cleaning, rinse thoroughly with potable water.

### Safety & Hazards



Wear Protective Eye Glasses, Chemical-Resistant Gloves and Waterproof Apron While Using Resque Plus

**Consult SDS for Further Safety Precautions**

**DOT Shipping Name:** UN 1814, Potassium Hydroxide Solution, 8, PG II

### Technical Information:

Appearance: Clear Red Liquid  
Odor: Mild Butyl  
pH: >12.0  
Foam: Moderate Foam

### Associated Products:

Improve Liquid Break, Laundry Pre-Soak & Alkalinity Booster  
Flash Floor Cleaner, Heavy Duty Powdered Concrete Cleaner  
Kleen-Safe, Highly Effective Heavy Duty Cleaner/Degreaser

### Resque Plus

#### Dilution Guidelines

Usage	Dilution
General Purpose Cleaning	1 - 4 Ounces Per Gallon
Foam Cleaning	2 - 8 Ounces Per Gallon
Heavy Grease & Oil	8 - 10 Ounces Per Gallon
Laundry Detergent	4 - 12 Ounces per 50 Pound Load

#### Titration Kit:

MRTK5000-Z, Alkalinity Titration  
1 Drop = 0.333 oz per gallon

Warning: Do Not Mix With Acidic Products. May Damage Painted Surfaces, Aluminum, Brass, Copper, Galvanized And/Or Other Soft Metals.

Products Manufactured By:



8707 Millergrove Drive • Santa Fe Springs, CA 90670  
(562) 695-1232 • FAX: (562) 699-8953