

CSD

Powdered CIP Detergent with Bleach

CSD is a heavy duty, low-foaming CIP detergent effective on oils, grease, sugary and proteinaceous soils. CSD can be used for CIP and spray cleaning of process tanks and hot milk lines in dairies, as a HTST cleaner in bakeries or a soak cleaner in food processing plants. CSD can be mixed with Detergent Concentrate when foaming applications are needed.

- **Heavy Duty Detergent with Bleach**
- **Useful in Industrial Dishwashing Machines**
- **Non-Silicate**
- **Rinses Easily**

Usage Directions: Dilute CSD in accordance with Dilution Guidelines chart.

CIP applications: Flush pipes with fresh water to remove loose soils. Heat CSD solution to 140°-150°F. Circulate solution through pipes for 10 - 25 minutes, or until all soils are removed from pipelines. Flush lines with fresh water. Fill pipelines with appropriate sanitizer.

Soak Applications: Add appropriate amount of CSD to cleaning bath. Heat solution, when possible, to 140°-150°F. Allow parts to soak for 10 - 25 minutes, or until all soils are removed from parts. Rinse parts with fresh water and follow with appropriate sanitizer.

Dishwashing Machine: Add appropriate amount of CSD to dish machine manually or through powder dispenser. CSD works best when used with hot water. Follow with rinsing agent and sanitizing rinse.

Safety & Hazards



Wear Protective Eye Glasses, Chemical-Resistant Gloves and Waterproof Apron While Using CSD

Consult SDS for Further Safety Precautions

DOT Shipping Name: UN1823, Sodium Hydroxide, solid. mixture, 8, PG II

Technical Information:

Appearance: Orange. Free flowing granules.

Odor:

pH: 12.0 - 13.0

Foam: Non-Foaming

Associated Products:

Detergent Concentrate, Heavy Duty Detergent & Foam Booster

MG 4-Quat, 5th Generation Quaternary Sanitizer & Disinfectant

MG Peracid 6, 5.6% Peroxyacetic Acid Sanitizer

Rinse Aid, Warewashing Rinse Additive & Sheeting Agent

CSD Dilution Guidelines	
Usage	Dilution
CIP Applications	1 - 4 Oz per Gallon Water
Soak Applications	2 - 6 Oz per Gallon Water
Dishwashing Machines	1 - 2 Oz Per Gallon Water

Warning: Do Not Mix With Acidic Products. May Damage Painted Surfaces, Aluminum, Brass, Copper, Galvanized And/OR Other Soft Metals.

Products Manufactured By:

